

Application No.: 09/901,972
Response to OA of 12/06/04

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of the claims:

1. (currently amended) A distributed data center system protocol comprising:

providing a client having a failure detector and a plurality of data centers each including a plurality of database servers;

selecting one of the plurality of data centers to be a primary data center with the other of the plurality of data centers to be a backup data center;

selecting one of the plurality of database servers in the primary data center to be a primary database server with the other of the plurality of database servers therein to be a backup database server and the plurality of database servers in the backup data center to be backup database servers;

providing communications from the client to the primary database server and the backup database servers;

selecting one of the backup database servers as a new primary database server when one of the backup database servers detects a failure of the primary database server;
and

when the primary database server receives a message from the client to start a new transaction, checking whether the primary database server has already executed another transaction corresponding to the new transaction to ensure that a job generates one committed transaction per database, providing further communications from the client to the new primary database server when the client suspects a failure of the primary database server; and

~~providing an abort operation from the client to the primary database server when the client suspects a failure of the primary database server.~~

2. (canceled)

3. (previously presented) A distributed data center system protocol comprising:

Application No.: 09/901,972
Response to OA of 12/06/04

providing a client having a failure detector and a plurality of data centers each including a plurality of database servers;

selecting one of the plurality of data centers to be a primary data center with the other of the plurality of data centers to be a backup data center;

selecting one of the plurality of database servers in the primary data center to be a primary database server with the other of the plurality of database servers therein to be a backup database server and the plurality of database servers in the backup data center to be backup database servers;

providing communications from the client to the primary database server and the backup database servers;

selecting one of the backup database servers as a new primary database server when one of the backup database servers detects a failure of the primary database server;

providing further communications from the client to the new primary database server when the client suspects a failure of the primary database server; and

checking whether the primary database server has already executed a transaction operation for a transactional job corresponding to the same transactional job before executing the transaction operation.

4. (original) The distributed data center system protocol as claimed in claim 1 wherein:

providing the plurality of database servers includes providing local databases therefor; and

providing the communications includes the primary database server sending a transaction operation to the local database and executing the transaction operation.

5. (original) The distributed data center system protocol as claimed in claim 1 including:

providing a transaction operation from the client to the primary database server and the backup database servers; and

executing the transaction operation and a second transaction operation in the same order both in the primary database server and the backup database server.

6. (original) The distributed data center system protocol as claimed in claim 1 including:

Application No.: 09/901,972
Response to OA of 12/06/04

providing first and second durability levels of operation wherein employing the first durability level in the primary database server executes the transaction operation faster than the second durability level of operation.

7. (original) The distributed data center system protocol as claimed in claim 1 wherein:
providing the plurality of database servers in the primary and backup data centers includes each of the plurality of database servers having failure detectors and the client having a failure detector with properties of strong completeness and eventual weak accuracy.

8. (original) The distributed data center system protocol as claimed in claim 1 wherein:
providing the client includes providing the client with disaster detectors with properties of strong completeness and eventual strong accuracy.

9. (original) The distributed data center system protocol as claimed in claim 1 wherein:
providing the plurality of database servers in the primary and backup data centers includes each of the plurality of database servers having disaster detectors with properties of strong completeness and strong accuracy.

10. (original) The distributed data center system protocol as claimed in claim 1 wherein:
providing the primary database server includes providing a local database therefor; and
executing a transaction operation includes the primary database server sending the transaction operation to the local database.

11. (currently amended) The distributed data center system protocol as claimed in claim 1 including: ~~A distributed data center system protocol comprising:~~
~~providing a client having a failure detector and a plurality of data centers each including a plurality of database servers;~~
~~selecting one of the plurality of data centers to be a primary data center with the other of the plurality of data centers to be a backup data center;~~

Application No.: 09/901,972
Response to OA of 12/06/04

~~_____ selecting one of the plurality of database servers in the primary data center to be a primary database server with the other of the plurality of database servers therein to be a backup database server and the plurality of database servers in the backup data center to be backup database servers;~~

~~_____ providing communications from the client to the primary database server and the backup database servers;~~

~~_____ selecting one of the backup database servers as a new primary database server when one of the backup database servers detects a failure of the primary database server;~~

~~_____ providing further communications from the client to the new primary database server when the client suspects a failure of the primary database server; and~~

~~_____ communicating from the primary database server to the backup database servers by broadcast communication of a transaction unique identification, statements associated with the transaction operation, and control information from the primary database server to the backup database servers.~~

12. (previously presented) A distributed data center system protocol comprising:

providing a client having a failure detector and a plurality of data centers each including a plurality of database servers;

selecting one of the plurality of data centers to be a primary data center with the other of the plurality of data centers to be a backup data center;

selecting one of the plurality of database servers in the primary data center to be a primary database server with the other of the plurality of database servers therein to be a backup database server and the plurality of database servers in the backup data center to be backup database servers;

providing communications from the client to the primary database server and the backup database servers;

selecting one of the backup database servers as a new primary database server when one of the backup database servers detects a failure of the primary database server;

providing further communications from the client to the new primary database server when the client suspects a failure of the primary database server;

Application No.: 09/901,972
Response to OA of 12/06/04

providing for only one primary data center and only one primary database server during a numbered epoch;

establishing an epoch number by one of the plurality of database servers when the one of the plurality of database servers in the backup data center detects a failure of the primary data center; and

determining the only one primary data center and the only one primary database server deterministically from the epoch number.

13. (previously presented) The distributed data center system protocol as claimed in claim 1 including:

providing for only one primary data center and only one primary database server during a numbered epoch;

establishing an epoch number by one of the plurality of database servers when the one of the plurality of database servers in the backup data center detects a failure of the primary data center;

broadcasting a current epoch number from the one of the plurality of database servers to the other of the plurality of database servers to change the epoch number;

determining the only one primary data center and the only one primary database server deterministically from the epoch number; and

providing a transaction operation to the only one primary data center and the only one primary database server for the epoch number.

14. (original) The distributed data center system protocol as claimed in claim 13 including:

performing a certification test in each of the plurality of database servers after receiving the broadcasting of the epoch number.

15. (previously presented) A distributed data center system protocol comprising:

providing a client having a failure detector and a plurality of data centers each including a plurality of database servers operatively interconnected;

Application No.: 09/901,972
Response to OA of 12/06/04

selecting one of the plurality of data centers to be a primary data center with the other of the plurality of data centers to be a backup data center;

selecting one of the plurality of database servers in the primary data center to be a primary database server with the other of the plurality of database servers in the primary data center to be a backup database server and the plurality of database servers in the backup data center to be backup database servers;

providing a transaction operation from the client to the primary database server and the backup database servers;

providing error messages from the backup database servers to the client indicating that the backup database servers are not the primary database server;

executing the transaction operation by the primary database server;

selecting one of the backup database servers as a new primary database server when one of the backup database servers detects a failure of the primary database server;

selecting one of the backup database servers as a new primary database server when one of the backup database servers suspects a failure of the primary database server;

providing the transaction operation from the client to the new primary database server when the client detects a failure or change of the primary database server;

executing the transaction operation by the new primary database server when the transaction operation is provided from the client to the new primary database server;

returning the result of the executed transaction operation from the new primary database server to the client; and

checking whether the primary database server has already executed a transaction operation for a transactional job corresponding to the same transactional job before executing the transaction operation.

16. (canceled).

17. (canceled).

18. (original) The distributed data center system protocol as claimed in claim 15 wherein:

Application No.: 09/901,972
Response to OA of 12/06/04

providing the plurality of database servers includes providing local databases therefor;

executing the transaction operation includes the primary database server sending the transaction operation to the local database and waiting for a reply;

executing the transaction operation includes waiting for a reply from the local database to the primary database server and sending the reply to the client;

executing the transaction operation includes sending a commit request to the primary database server in response to the reply; and

executing the transaction operation includes the primary database server broadcasting a transaction unique identification, SQL statements associated with the transaction operation, and control information to the backup data server in the primary data center, and the plurality of backup data servers in the backup data center.

19. (original) The distributed data center system protocol as claimed in claim 15 including:

providing a second transaction operation from the client to the primary database server and the backup database servers; and

executing the transaction operation and the second transaction operation in the same order both in the primary database server and the backup database server.

20. (original) The distributed data center system protocol as claimed in claim 15 including:

providing first and second durability levels of operation wherein:

employing the first durability level in the primary database server executes the transaction operation faster than the second durability level of operation and

employing the second durability level in the primary database server executes the transaction operation with the assurance that if the primary data center suffers a disaster, the plurality of backup databases in the backup data center will receive the transaction operation.

21. (original) The distributed data center system protocol as claimed in claim 15 wherein:

Application No.: 09/901,972
Response to OA of 12/06/04

providing the plurality of database servers in the primary and backup data centers includes each of the plurality of database servers having failure detectors and the client having a failure detector with the properties of:

strong completeness wherein, if the primary database server fails at time t , then there is a time $t' > t$ after which the primary database server is permanently suspected of failure by the client and by the backup database server; and

eventual weak accuracy wherein, if the primary database server that does not fail, then there is a time after which the primary database server is never suspected of failure by the client and by the backup database server.

22. (original) The distributed data center system protocol as claimed in claim 15 wherein:

providing the client includes providing the client with disaster detectors with the properties of:

strong completeness wherein, if the primary data center fails at time t , then there is a time $t' > t$ after which the primary data center is permanently suspected of failure by the client; and

eventual strong accuracy wherein, if the primary data center that does not fail, then there is a time after which the primary data center is never suspected of failure by the client.

23. (original) The distributed data center system protocol as claimed in claim 15 wherein:

providing the plurality of database servers in the primary and backup data centers includes each of the plurality of database servers having disaster detectors with the properties of:

strong completeness wherein, if the primary data center fails at time t , then there is a time $t' > t$ after which the primary data center is permanently suspected of failure by the backup database servers; and

strong accuracy wherein, if the primary data center that does not fail, then the primary data center is never suspected of failure by the backup database servers.

24. (original) The distributed data center system protocol as claimed in claim 15 wherein:

Application No.: 09/901,972
Response to OA of 12/06/04

providing the primary database server includes providing a local database therefor; and

executing the transaction operation includes the primary database server sending the transaction operation to the local database.

25. (currently amended) The distributed data center system protocol as claimed in claim 15 including:

- ~~—— A distributed data center system protocol comprising:~~
- ~~—— providing a client having a failure detector and a plurality of data centers each including a plurality of database servers operatively interconnected;~~
- ~~—— selecting one of the plurality of data centers to be a primary data center with the other of the plurality of data centers to be a backup data center;~~
- ~~—— selecting one of the plurality of database servers in the primary data center to be a primary database server with the other of the plurality of database servers in the primary data center to be a backup database server and the plurality of database servers in the backup data center to be backup database servers;~~
- ~~—— providing a transaction operation from the client to the primary database server and the backup database servers;~~
- ~~—— providing error messages from the backup database servers to the client indicating that the backup database servers are not the primary database server;~~
- ~~—— executing the transaction operation by the primary database server;~~
- ~~—— selecting one of the backup database servers as a new primary database server when one of the backup database servers detects a failure of the primary database server;~~
- ~~—— selecting one of the backup database servers as a new primary database server when one of the backup database servers suspects a failure of the primary database server;~~
- ~~—— providing the transaction operation from the client to the new primary database server when the client detects a failure or change of the primary database server;~~
- ~~—— executing the transaction operation by the new primary database server when the transaction operation is provided from the client to the new primary database server;~~

Application No.: 09/901,972
Response to OA of 12/06/04

~~_____returning the result of the executed transaction operation from the new primary database server to the client; and~~

~~_____communicating from the primary database server to the backup database servers by broadcast communication of a transaction unique identification, statements associated with the transaction operation, and control information from the primary database server to the backup database servers.~~

26. (original) The distributed data center system protocol as claimed in claim 15 including:

providing for only one primary data center and only one primary database server during a numbered epoch;

establishing an epoch number by one of the plurality of database servers when the one of the plurality of database servers in the backup data center detects a failure of the primary data center;

establishing an epoch number by one of the plurality of database servers when the one of the plurality of database servers in the primary or backup data centers detects a failure of the primary database server;

establishing an epoch number by one of the plurality of database servers when the one of the plurality of database servers in the primary or backup data center suspects a failure of the primary database server;

determining the only one primary data center and the only one primary database server deterministically from the epoch number; and

providing the transaction operation to the only one primary data center and the only one primary database server for the epoch number.

27. (previously presented) The distributed data center system protocol as claimed in claim 15 including:

providing for only one primary data center and only one primary database server during a numbered epoch;

Application No.: 09/901,972
Response to OA of 12/06/04

establishing an epoch number by one of the plurality of database servers when the one of the plurality of database servers in the backup data center detects a failure of the primary data center;

establishing an epoch number by one of the plurality of database servers when the one of the plurality of database servers in the primary or backup data centers detects a failure of the primary database server;

establishing an epoch number by one of the plurality of database servers when the one of the plurality of database servers in the primary or backup data center suspects a failure of the primary database server;

broadcasting a current epoch number from the one of the plurality of database servers to the other of the plurality of database servers to change the epoch number;

determining the only one primary data center and the only one primary database server deterministically from the epoch number; and

providing the transaction operation to the only one primary data center and the only one primary database server for the epoch number.

28. (original) The distributed data center system protocol as claimed in claim 27 including:

performing a certification test in each of the plurality of database servers after receiving the broadcasting of the epoch number wherein:

executing the transaction operation includes broadcasting the transaction operation and the epoch number from the primary database server; and

committing the completed transaction operation when the certification test determines the epoch number in the new primary database server is the same as the epoch number of the transaction operation.

29. (new) A distributed data center system protocol comprising:

providing a client and a plurality of data centers each including a plurality of database servers;

specifying, by the client, conditions under which lost transactions are acceptable in order to increase performance;

Application No.: 09/901,972
Response to OA of 12/06/04

selecting one of the plurality of database servers to be a primary database server
with the other of the plurality of database servers to be backup database servers;

selecting one of the backup database servers as a new primary database server
when one of the backup database servers detects a failure of the primary database server;
and

when the primary database server receives a message from the client to start a
new transaction, checking whether the primary database server has already executed
another transaction corresponding to the new transaction to ensure that a job generates
one committed transaction per database.

30. (new) The distributed data center system protocol of claim 29 wherein only the
primary database server gets requests from the client while the other of the plurality of
database servers interact with the primary database server and not the client.